



Geschweißte maßgewalzte Präzisionsstahlrohre nach EN 10305-3 (DIN 2394)

Electric Welded Size-rolled Precision Steel Tubes acc. to EN 10305-3 (DIN 2394)

Stand: 2014-02 V 1.00

		Wanddicke (T) / Wall Thickness (WT) **																
		mm		3,500 3,660 4,000 4,050 4,500 4,650 5,000 5,500 6,000														
		inch		0,138 0,144 0,157 0,159 0,177 0,183 0,197 0,217 0,236 0,000 0,000 0,000 0,000 0,000 0,000 0,000 0,000 0,000														
Nennmaß Nominal Size	zul. Ab- weichung Tolerance	Nennmaß Nominal Size	zul. Ab- weichung Tolerance															
10,00	± 0,08	0,394	± 0,003															
12,00		0,472																
12,70		0,500																
14,00		0,551																
15,00		0,591																
15,88		0,625																
16,00		0,630																
18,00		0,709																
19,05		0,750																
20,00		0,787																
22,00		0,866																
22,23		0,875																
23,00		0,906																
24,00		0,945																
25,00		0,984																
25,40		1,000																
26,00		1,024																
28,00		1,102																
26,99		1,063																
30,00		1,181																
31,75	± 0,15	1,250	± 0,006															
32,00		1,260																
33,00		1,299																
34,00		1,339																
34,93		1,375																
35,00		1,378																
38,00		1,496																
38,10		1,500																
40,00		1,575																
41,28	± 0,20	1,625	± 0,008															
42,00		1,654																
44,45		1,750																
45,00		1,772																
46,00		1,811																
47,63		1,875																
48,00		1,890																
49,00		1,929																
50,00		1,969																
50,80	± 0,25	2,000	± 0,010															
51,00		2,008																
52,00		2,047																
53,96		2,124																
55,00		2,165																
56,00		2,205																
57,15		2,250																
60,00		2,362																
60,03	± 0,30	2,363	± 0,012															
63,50		2,500																
65,00		2,559																
69,85		2,750																
70,00		2,756																
73,00	± 0,35	2,874	± 0,014															
75,00		2,953																
76,20		3,000																
82,55	± 0,40	3,250	± 0,016															
85,00		3,346																
88,90		3,500																
90,00		3,543																
95,00	± 0,45	3,740	± 0,018															
100,00		3,937																
102,00	± 0,50	4,016	± 0,020															
108,00		4,252																
110,00		4,331																
114,30		4,500																

Außendurchmesser (D) / Outside Diameter (OD) **

Weitere Abmessungen und ** Toleranzen auf Anfrage / Other dimensions and ** tolerances on request
 =Standard Lieferprogramm / Standard Product Range
 =Kunden Lieferprogramm / Customer Product Range