



Geschweißte-gezogene Präzisionsstahlrohre nach EN 10305-2 (DIN 2393)
Cold Drawn Welded Precision Steel Tubes acc. to EN 10305-2 (DIN 2393)

Stand: 2014-02 V 1.00

		Wanddicke (T) / Wall Thickness (WT) **																									
		mm		inch		3,500	3,810	4,000	4,190	4,500	4,570	4,780	5,000	5,160	5,250	5,500	5,590	6,000	6,500	7,000	7,500	8,000	9,000	#####			
						0,138	0,150	0,157	0,165	0,177	0,180	0,188	0,197	0,203	0,207	0,217	0,220	0,236	0,256	0,276	0,295	0,315	0,354	0,394			
Nennmaß Nominal Size	± zul. Ab- weichung Tolerance	Nennmaß Nominal Size	± zul. Ab- weichung Tolerance																								
10,00	± 0,08	0,394	± 0,003																								
12,00		0,472																									
12,70		0,500																									
14,00		0,551																									
15,00		0,591																									
15,88		0,625																									
16,00		0,630																									
18,00		0,709																									
19,05		0,750																									
20,00		0,787																									
22,00		0,866																									
22,23		0,875																									
23,00		0,906																									
24,00		0,945																									
25,00		0,984																									
25,40		1,000																									
26,00		1,024																									
28,00		1,102																									
28,58		1,125																									
30,00		1,181																									
31,75	± 0,15	1,250	± 0,006																								
32,00		1,260																									
33,00		1,299																									
34,00		1,339																									
34,93		1,375																									
35,00		1,378																									
38,00		1,496																									
38,10		1,500																									
40,00		1,575																									
41,28	± 0,20	1,625	± 0,008																								
42,00		1,654																									
44,45		1,750																									
45,00		1,772																									
46,00		1,811																									
47,63		1,875																									
48,00		1,890																									
49,00		1,929																									
50,00		1,969																									
50,80	± 0,25	2,000	± 0,010																								
51,00		2,008																									
52,00		2,047																									
53,96		2,124																									
55,00		2,165																									
56,00		2,205																									
57,15		2,250																									
60,00		2,362																									
60,03	± 0,30	2,363	± 0,012																								
63,50		2,500																									
65,00		2,559																									
69,85		2,750																									
70,00		2,756																									
73,00	± 0,35	2,874	± 0,014																								
75,00		2,953																									
76,20		3,000																									
80,00		3,150																									
82,55	± 0,40	3,250	± 0,016																								
85,00		3,346																									
88,90		3,500																									
90,00		3,543																									
95,00	± 0,45	3,740	± 0,018																								
95,25		3,750																									
100,00		3,937																									
110,00	± 0,50	4,331	± 0,020																								
120,00		4,724																									

Außendurchmesser (D) / Outside Diameter (OD) **

Weitere Abmessungen und ** Toleranzen auf Anfrage / Other dimensions and ** tolerances on request

Standard Lieferprogramm / Standard Product Range

Kunden Lieferprogramm / Customer Product Range